



STEREO INTEGRATED AMPLIFIER A-302U CLASSIC WITH BLUETOOTH



FRONT VIEW



REAR VIEW

**SMOOTH SOUND, EASE OF USE & RELIABILITY MEET LUSTROUS FINISH AND SIMPLE ELEGANCE.
BRUSHED ALUMINIUM ANODIZED WRAP AROUND BODY & TOP COVER**

INPUTS AVAILABLE ON AMPLIFIER: PHONO, LINE 1, LINE 2, USB, DIGITAL (COAXIAL & OPTICAL), BLUETOOTH AND AN MP3 INPUT ON FRONT PANEL FOR EASY CONNECTIVITY TO YOUR PHONE /TABLET OR ANY OTHER DIGITAL DEVICE.

HEADPHONE SOCKET AVAILABLE FOR PERSONAL LISTENING.

DIRECT SWITCH AVAILABLE TO BYPASS TONE CONTROLS.

OUTPUTS AVAILABLE FOR 2 PAIRS OF SPEAKERS – EITHER ONE PAIR, OR BOTH PAIRS OF SPEAKERS CAN BE PLAYED SIMULTANEOUSLY IF THEY ARE RATED AT 8 OHM IMPEDANCE.

LINE OUT SOCKETS AVAILABLE TO DAISY CHAIN TO ANOTHER AMPLIFIER OR TO TAKE AN OUTPUT TO AN **ACTIVE SUBWOOFER** AND RECORD OUT SOCKETS AVAILABLE TO RECORD SIGNAL INTO ANY RECORDING DEVICE.

POWER OUTPUT : 45 WATT RMS/CH @ 8 OHMS IMPEDANCE AND 75 WATT RMS/CH @ 4 OHMS IMPEDANCE

TOTAL HARMONIC DISTORTION :< 0.5%

INPUT IMPEDANCE : 47K OHMS

INPUT SENSITIVITY :< 300 mV

SIGNAL TO NOISE RATIO :> 80 dB

DIMENSIONS : 435mm (W) x 360mm (D) x 70mm (H)

TREBLE :< 10 dB

BASS :< 10 dB

LOUDNESS : + 8 dB @ 50 Hz & + 4 dB @ 10 KHz

FREQUENCY RESPONSE: 20 Hz - 20KHz

POWER REQUIREMENT : AC 230V/50 Hz

Note : 1. Input Selection Buttons need to be long Pressed for 3-4 seconds for effecting change.

2. As part of our continuing programme to improve the design and quality of all our products we shall be free to make changes in the design and specifications without any notice.